

SBP30 Display-Film 380g

- Description:

High-quality frontlit PET display film with gray backing for high opacity.
- Application:

For roll-up displays and display graphics.
- Properties:

The SBP30 has good flatness, is scratch-resistant, tear-resistant, and opaque thanks to its gray backing.
- Inks and printers:

Universally applicable for printers with solvent, latex, and UV-curing inks.
- Printing:

Allow the material to acclimatize to room temperature (> 20°C) for at least 2 hours in the printer room before printing. Ensure a dust-free printing environment and avoid fingerprints on the printing surface by wearing cotton gloves. Check that the device and temperature settings are correct by making a test print. Depending on the selected printing method and ink limit, we recommend laying the film flat after printing until it is completely dry.
- Storage:

Store the material immediately after each use to prevent contamination and curling. Repack the material in the protective film and store the roll upright in a light-protected and dust-free environment at 40 to 60% relative humidity and 15 to 25°C room temperature.

Technical Data:

Feature	Value	Method
Weight	380 g/m²	DIN 53352
Tempature range	-20°C - +70°C	DIN 53372
Fire protection certificate	None	

Note:

The technical data refers to the unprinted material. Our information does not release you from conducting your own tests to check suitability for your application. We have no influence on the properties and durability of the inks; please also observe the printer manufacturer's instructions. The data sheet is based on manufacturer information; Alphaset accepts no liability. Subject to technical changes and typographical errors.
Version June 2025 MR