

SFP230G Glossy photo paper, 225g

- Description:

Glossy PE-coated photo paper.
- Application:

Photorealistic large-format images and advertising graphics for indoor use.
- Properties:

The SFP230G impresses with its excellent image quality, good flatness and stiffness and high whiteness. The material allows for fast ink drying. The surface has good scratch resistance and splash and water resistance and can also be used without a protective laminate..
- Inks and Printers:

Universally applicable for printers with solvent, UV, and latex ink.
- Printing:

Allow the material to acclimatize in the printer room for at least 2 hours before printing hours at room temperature (> 20°C). The print side should be facing outwards. Ensure for a dust-free printing environment and avoid fingerprints on the printing surface by wearing cotton gloves.
- Lamination:

Suitable for cold lamination up to 60°C. Please ensure that the print is completely dry before laminating (we recommend leaving the paper open for 24 hours).
- Storage:

Store the material immediately after printing to prevent soiling and curling. Repack the material in the protective film and store the roll upright in a light-protected and dust-free environment at 30 to 65% relative humidity and 10°C to 30°C room temperature. The shelf life is 24 months.

Technical data:

Feature	Value	Method
Total weight:	225 g	DIN ISO 536
Thickness	220 µm	DIN ISO 534
Gloss	> 73 (60°GE)	DIN ISO 2813
Whiteness	L*94.0 a*0.8 b*-6.0	DIN ISO 13655, M0

- Note:

The technical data refers to the unprinted material. Our information does not release you from conducting your own tests to check suitability for your application. We have no influence on the properties and durability of the inks; please also note the printer manufacturer's instructions. The data sheet is based on manufacturer's information; Alphaset accepts no liability. Subject to technical changes and typographical errors.
Version September 2024