

SFP230S Photo paper satin, 225g

- Description:

Satin PE-coated photo paper
- Application:

Photorealistic large-format images, posters, and advertising graphics for indoor use.
- Properties:

The SFP230S impresses with its excellent image quality, good flatness and stiffness and high whiteness. The material allows for fast ink drying. The surface has good scratch resistance and splash and water resistance and can also be used without a protective laminate.
- Inks and printers:

Universally applicable for printers with solvent and latex ink.
- Printing:

Allow the material to acclimatize to room temperature (> 20°C) for at least 2 hours in the printer room before printing. The print side is on the outside. Ensure a dust-free printing environment and avoid fingerprints on the print surface by wearing cotton gloves.
- Lamination:

Suitable for cold lamination up to 60°C. Please ensure that the print is completely dry before laminating (recommended 24 hours with the paper laid flat).
- Storage:

Store the material immediately after printing to prevent contamination and curling. Repack the material in the protective film and store the roll upright in a light-protected and dust-free environment at 35 to 65% relative humidity and 10°C to 25°C room temperature. The shelf life is 24 months.

Technical Data:

Feature	Value	Method
Total weight	225 g	DIN ISO 536
Thickness	215 µm	DIN ISO 534
Opacity	>94%	DIN ISO 2469
Gloss	22 (60°GE)	DIN ISO 2813
Whiteness	L*93.7 a*-0.3 b*-1.6 delta b*11.4	DIN ISO 2469

Note:

The technical data refers to the unprinted material. Our information does not release you from conducting your own tests to check suitability for your application. We have no influence on the properties and durability of the inks; please also note the printer manufacturer's instructions. The data sheet is based on manufacturer's information; Alphaset accepts no liability. Subject to technical changes and typographical errors.
Version September 2024