

Classification report

This document is an authorized English version of the reaction to fire classification report RC-RF 0019/2021-URF issued by the Reaction to Fire Testing Laboratory of the National Laboratory of Civil Engineering (LNEC/ EM-URF).

CLASSIFICATION OF REACTION TO FIRE PERFORMANCE IN ACCORDANCE WITH EN 13501-1:2018-en (and COMMISSION DELEGATED REGULATION (EU) 2016/364 of 1 July 2015

1 | Identification:

Description of the sample:

Self-adhesive vinyl films (monomeric PVC), **“PVC Vinyl 100 microns permanent blackout”, white glossy, white matte**, smooth finish, with acrylic adhesive, for use on non-porous flat surfaces (excluding floors).

Classification report No:

0019/2021-URF

Date of issue:

2021-03-16

2 | Introduction:

This classification report defines the reaction to fire classification assigned to the self- - adhesive monomeric PVC films for promotional and decorative applications **“PVC Vinyl 100 microns permanent blackout”**. smooth finish (soft calendered), white matte or white glossy, with acrylic adhesive and removable Double Sided PE, for flat and non-porous surfaces (excluding floorings), in accordance with the procedures given in EN 13501-1:2018 - *"Fire classification of construction products and building elements – Part 1: Classification using data from reaction to fire tests"* (and COMMISSION DELEGATED REGULATION (EU) 2016/364 of 1 July 2015).

LNEC's Reaction to Fire Testing Laboratory (LNEC/EM-URF) is accredited by IPAC (L0488-Ensaíos) to perform the fire tests (vd. 4) supporting the assigned classification.

3 | Details of the classified Product:

3.1 General

The classified products for decorative and promotional applications, for flat and non-porous surfaces (excluding floors), consisted of self-adhesive monomeric PVC films **“PVC Vinyl 100 microns permanent blackout”** and, smooth finish (soft calendered), white matte or white glossy.

Classification report

3.2 Product description

In accordance with the information and the Technical Data Sheets supplied by the sponsor, the tested product samples presented the following generic characteristics:

(Sample 61/2020-1) – “PVC Vinyl 100 microns permanent blackout”:

- Commercial designation: **“PVC Vinyl 100 microns permanent blackout”**
- Material (film): self-adhesive vinyl, monomeric PVC film
- Finish reference - **Glossy**
- Finish: brushed
- Colour : **white**
- Mass per unit area (**nominal** value): 128 g/m² (± 10%)
- Thickness: 100 µm (± 10%)
- Adhesive: clear acrylic
- Liner (removable): Double Sided PE
 - Mass per unit area (**nominal** value): 125 g/m² (± 10%)
 - Thickness (**nominal** value): 118 µm (± 10%)
- Field of application: flat, smooth non porous surfaces (excluding floors)

(Sample 61/2020-1) – “PVC Vinyl 100 microns permanent blackout”

- Commercial designation: **“PVC Vinyl 100 microns permanent blackout”**
- Material (film): self-adhesive vinyl, monomeric PVC film
- Finish reference - **matte**
- Finish: brushed
- Colour : **white**
- Mass per unit area (**nominal** value): 128 g/m² (± 10%)
- Thickness: 100 µm (± 10%)
- Adhesive: clear acrylic
- Liner (removable): Double Sided PE
 - Mass per unit area (**nominal** value): 125 g/m² (± 10%)
 - Thickness (**nominal** value): 118 µm (± 10%)
- Field of application: flat, smooth non porous surfaces (excluding floors)

Classification report

4.1 | Test reports and test results in support of classification:

Name of Laboratory	Name of sponsor	Report No.	Test method and date
LNEC/EM-URF		0006/2021-URF	EN ISO 11925-2:2020
		0007/2021-URF	EN ISO 11925-2:2020
		0032/2021-URF	EN ISO 11925-2:2020
		0016/2021-URF	EN 13823:2020
		0031/2021-URF	EN 13823:2020

4.2 Test results:

Test method(s)	Parameter	No. test specimens	Results	
			Continuous parameter mean values * (individual values)	Compliance with parameters
EN 13823:2020 (SBI test)	FIGRA _{0,2MJ} (W/s)	1 + 1 + 1 + 1 (1)	1.2 (--- / 4.9 / --- / ---)	YES
	FIGRA _{0,4MJ} (W/s)		1.2 (--- / 4.9 / --- / ---)	(YES)
	LFS < edge		YES (YES / YES / YES / YES)	YES
	THR _{600s} (MJ)		0.9 (0.6 / 0.9 / 0.8 / 1.1)	YES
	SMOGRA (m ² /s ²)		--- (--- / --- / --- / ---)	YES
	TSP _{600s} (m ²)		25 (20 / 22 / 23 / 33)	YES
	FDP		NO (NO / NO / NO / NO)	YES
Test method(s)	Parameter	No. test specimens	Results	
			Continuous parameter (individual values)	Compliance with parameters
EN ISO 11925-2:2020	Fs	2 + 2 ⁽²⁾ 3 + 3 ⁽²⁾ 1 + 1 ⁽²⁾	< 20	YES (Fs ≤ 150 mm)
Edge and surface exposure to flame	Flaming droplets/particles		NO	YES
Exposure time: 30 s	Ignition of the filter paper		NO	YES

Classification report

5 | Classification and field of application:

5.1 Reference of classification

This classification has been carried out in accordance with clause 11 of EN 13501-1:2018, December 2018 (and criteria defined in COMMISSION DELEGATED REGULATION (EU) 2016/364 of 1 July 2015).

5.2 Classification

Self-adhesive monomeric PVC films for promotional and decorative application “**PVC Vinyl 100 microns permanent blackout**” white matte or white glossy, smooth finish, in relation to their reaction to fire behaviour are classified (*see also* 5.3):

B

The additional classification in relation to smoke production is:

S1

The additional classification in relation to flaming droplets /particles is:

D0

The format of the reaction to fire classification **except for floorings** is:

Fire behaviour		Smoke production			Flaming droplets / particles	
B	-	s	1	,	d	0

i.e., **B-s1, d0**

Reaction to fire classification: B-s1, d0

5.3 Field of application:

This classification is valid for self-adhesive monomeric PVC films for promotional and decorative applications “**PVC Vinyl 100 microns permanent blackout**” colour **white, matte** or **glossy**, smooth finish, when **applied directly** on **non-combustible surfaces** (classes **A1** or **A2-s1, d0**) having a density greater than 1350 kg/m³ and a thickness equal or greater than 9 mm.

Classification report

This classification is **not applicable** to uses of the product over existing coatings, and to painted or printed monomeric PVC films, and is also valid for **PVC Vinyl** (monomeric PVC) films, with the following characteristics:

- Mass per unit area (**nominal** value): $\leq 145 \text{ g/m}^2$
- Thickness (**nominal** value): $\leq 110 \text{ }\mu\text{m}$
- Colour: **white**
- Finish: smooth, **matte** or **glossy**